



Technical specifications

Tiller®-liftmobile LM75B



| | |
|---------------------|---|
| Max. liftcapacity: | 75 kg |
| Liftingspeed: | 100 mm/s |
| Max. liftingheight: | 1.10 m |
| Noseplate depth: | 0.06 m |
| Noseplate width: | 0.30 m |
| Weight: | 49 kg |
| Height: | 1.55 m |
| Width: | 0.52 m |
| Material: | coated steel |
| Tyre size: | 4.10/3.50 - 4 |
| Battery type: | NiMH |
| Voltage: | 24 V |
| Charger voltage: | 110V - 220V |
| Recharging time: | 8 hours at full discharge, automatically switch to trickle charge |

This accessory gives the liftmobile a specific application for transporting and lifting (beer) casks.

Certification

The liftmobile is CE certified. This means that the product complies with the relevant regulations within the European Economic Area (EEA: the European Union plus Liechtenstein, Norway and Iceland).

Machinery Directive (2006/42/EG)
EMC Directive (2004/108/EG)
Low Voltage Directive (2006/95/EG)

For the design and manufacture:
NEN-EN-ISO 12100-1; NEN-EN-ISO 12100-2;
NEN-EN-IEC 60204-1; NEN-EN 574;
NEN-EN 349; NEN-EN-IEC 61000-6-2; NEN-EN-IEC 61000-6-4

For the risk assessment:
NEN-EN-ISO 14121-1; NPR/ISO-TR 14121-2

Tiller BV
Den Haag, Netherlands
+31 (0) 15 - 310 6 999
www.tiller.eu